



**2 Bore code**

- B** without keyway
- K** with keyway

**4 Type**

- A** without handle
- D** with revolving handle

**1**

**3**

| d <sub>1</sub> | d <sub>2</sub> H7 Bore |    | d <sub>3</sub> | d <sub>4</sub> | d <sub>5</sub> | b  | l <sub>1</sub> -0,5 | l <sub>2</sub> -0,5 | l <sub>3</sub> ≈ | l <sub>4</sub> ≈ | r   | Ø Handle | No. of spokes |
|----------------|------------------------|----|----------------|----------------|----------------|----|---------------------|---------------------|------------------|------------------|-----|----------|---------------|
| 100            | 10                     | 12 | 25             | 19             | 28             | 15 | -                   | 23                  | 28               | 54,5             | 37  | 16       | 3             |
| 125            | 12                     | 14 | 24             | 20             | 30             | 18 | 1                   | 25                  | 35               | 67               | 47  | 20       | 3             |
| 140            | 14                     | 16 | 32             | 24             | 36             | 20 | 3                   | 26                  | 35               | 67               | 53  | 20       | 3             |
| 160            | 14                     | 16 | 32             | 24             | 37             | 22 | 5                   | 28                  | 40               | 83               | 59  | 25       | 3             |
| 200            | 18                     | 20 | 40             | 31             | 45             | 24 | 4                   | 33                  | 45               | 83               | 76  | 25       | 3             |
| 250            | 22                     | 24 | 49             | 38             | 56             | 29 | 7                   | 36                  | 58               | 105,5            | 98  | 32       | 3             |
| 300            | 26                     | 30 | 58             | 47             | 70             | 32 | 2                   | 40                  | 65               | 105,5            | 113 | 32       | 3             |

**Specification**

- Plastic  
Duroplast (Phenolic PF)  
- reinforced  
- temperature resistant up to 110 °C  
- black, shiny finish  
- Moulding flash removed and polished
- Hub bush  
Steel, blackened
- Threaded bush  
Brass
- Revolving handles DIN 98  
Plastic, Technopolymer  
black, matt
- *Keyway P9 DIN 6885* → Page 1124
- *ISO-Fundamental Tolerances* → Page 1132
- *Strength properties* → Page 1138
- *Plastic characteristics* → Page 1141
- **RoHS compliant**

**Information**

Face and bore are machined **after** the steel insert is pressed in, resulting in concentricity and squareness of rim.

They are also available without bore.

see also...

- *Countersunk washers GN 184 (for axial fixing)* → Page 542

How to order

**GN555-160-K16-D**

|          |                |
|----------|----------------|
| <b>1</b> | d <sub>1</sub> |
| <b>2</b> | Bore code      |
| <b>3</b> | d <sub>2</sub> |
| <b>4</b> | Type           |

1.1  
1.2  
1.3  
1.4  
1.5  
1.6  
1.7  
1.8  
1.9